

CLOCK

LIGATURE RESISTANT

Safe & Secure Lighting

ToughLITE
part of the Industrial Control System Group



DESCRIPTION

Ideally suited for high-risk areas like cell environments where the detained person is left on their own. Designed to be ligature resisting, very robust and secure. Supplied in a standalone housing or part of a full luminaire cornice version giving a wall to wall solution.

Clearly visible from over 10m in distance. Fully automatic and can be synchronised with up to 900 other clocks making sure continuity across the whole site. Automatic comfort brightness and British summer time adjustment with 16 million colours available. Battery backup memory in case of power failure. Setup and configuration is by wireless connection without the need to access the clock internally. It comes as standard in a 300mm width housing, other sizes are available upon request.

KEY FEATURES

- Ligature resisting
- Suitable for cell and high-risk areas
- Comes as a standalone clock or full system
- 12-24 hour setting (12 hour advised)
- Automatic time setting
- Automatic British Summer Time adjustment
- Automatic brightness
- Maintenance free
- 16 million possible colours

SPECIFICATION

- High impact IK10++ / Ingress protection IP65
- Polycarbonate TP(a) fire-retardant diffuser
- Body manufactured from 1.2mm steel
- Faceplate manufactured from 4mm steel
- RAL9010 polyester powder coat textured finish
- Hundredth second accuracy
- 50mm clear digits
- Battery backup
- Standalone or up to 900 device sync'd
- Wireless install setup
- Manufactured in the UK
- Full 5 year warranty

STANDALONE CLOCK

As standard the clock comes in a 45 degree angled housing for in cell use. Default width is 300mm. Other sizes available upon request.

FULL SYSTEM CLOCK

Able to be incorporated into a full cornice system. 128 clocks can be synchronised using the ToughLITE SYNC box.



	Length	Wattage	Weight	Part No
STANDALONE (STANDARD)	300mm	2w	5kg	TLCC300S
STANDALONE (BESPOKE)	XXX mm	2w	xxkg	TLCCxxxS
FULL SYSTEM	XXX mm	2w	xxkg	TLCCxxxF

ADDITIONAL ITEMS

ToughLITE SYNC Box Required for automatically adjustment from 1 to 128 clocks. Able to sync clocks up to 1km apart.

	Length	Height	Weight	Part No
SYNC Box	164mm	70mm	300g	TLCCSYNC

